C3325



- Washdown WC
- 6 litres (SF) & 6/3 litres (DF)
- S Trap : 250 mm
- P Trap : 190 mm
- Size : 730 x 675 x 360 x mm
- WELS

C3312 S



- Syphonic WC
- 6 litres (SF)
- S Trap : 305 mm
- Size : 705 x 745 x 383 mm

C838S / T838P



- 6 litres
- S Trap : 250 mm
- P Trap : 190 mm
- Size : 810 x 705 x 400 mm

C85 / T85P



- 6 litres (SF) & 4.5/3 litres (DF)
- S Trap : 250 mm
- P Trap : 190 mm
- Size : 765 x 680 x 375 mm
- WELS

C562S / T563P



- 6 litres (SF) & 6/3 litres (DF)
- S Trap : 140 mm
- P Trap : 190 mm
- Size : 780 x 620 x 365 mm

C89S / T563P



- 6 litres (SF) & 4.5/3 litres (DF)
- S Trap : 180 mm
- P Trap : 190 mm
- Size : 790 x 650 x 365 mm
- WELS

C10S / T80P



- 6 litres (SF) & 6/3 litres (DF)
- S Trap : 250 mm
- P Trap : 190 mm
- Size : 820 x 740 x 400 mm

C16SU / T820P



- 6 litres (SF) & 6/3 litres (DF)
- S Trap : 250 mm ; P Trap : 190 mm
- Size : 1045 x 730 x 360 mm
- Option : Type of Cisterns
  - a) T820P- Ceramic Cistern (P/B)
  - b) T740 - Ceramic Cistern (L/H)
  - c) LT5 - Plastic Cistern

C66S / T74BFB(LR) (Handicapped WC)



- 6 litres
- S Trap : 95 mm
- P Trap : 190 mm
- Size : 855 x 710 x 355 mm

C123S / T820P (Children WC)



- 6 litres (SF) & 6/3 litres (DF)
- S Trap : 305 mm
- P Trap : 175 mm
- Size : 1045 x 700 x 310 mm







C85C



- Back Inlet
  (For installation with concealed flush valve)
- 6 litres
- S Trap : 175 mm
- P Trap : 190 mm
- Size : 400 x 580 x 360 mm
- WELS

C28T (Top Inlet)



(For installation with exposed flush valve)
- 6 litres
- S Trap : 65 mm; P Trap : 190 mm
- Size : 390 x 445 x 375 mm
- Available : C28C (Back Inlet)
  (for installation with concealed flush valve)

C1153C (Back Inlet)



(For installation with concealed flush valve)
- 6 litres
- P Trap : 190 mm
- For installation with
- Concealed Flush Valve
- Size : 415 x 575 x 365 mm
- WELS

U24 / UF3D



- Top Inlet urinal
- For installation with UF3D Flush Valve
- Size : 620 x 315 x 330 mm
- Available :
  a) U24EX : With cleansing nozzle
  b) U24UC : Back Inlet
  option : SSU33 sensor flush valve or
  : UFSMP (B) manual flush valve

U22 / UF2D



- Top Inlet urinal
- For installation with UF2D Flush Valve
- Size : 570 x 275 x 360 mm

C337S



- Integrated squatting pan
- S Trap : 85mm ; P Trap : 170mm
- For installation with :
  a) SSW66 (N) sensor concealed flush valve
  b) CF110MPVD concealed flush valve
  c) CF10MVD exposed flush valve
  d) T740 High Level Ceramic Cistern (L/H)
  e) T740P Mid Level Ceramic Cistern (P/B)

C336



- Integrated squatting pan
- Loose : S Trap / P Trap
- S Trap : 265 mm
- P Trap : 178 mm
- For installation with :
  a) T740 High Level Ceramic Cistern (L/H)
  b) T740P Mid Level Ceramic Cistern (P/B)

C338 / HT5



- Squatting pan
- HT5 plastic cistern
- Loose : S Trap / P Trap
- S Trap : 265 mm
  P Trap : 178 mm



WGFA310111CP
SSW66 (N)
Sensor WC Flush Valve
With Override Button



WGFA310112CP
SSU33 (N)
Sensor Urinal Flush Valve
With Override Button



WGFA310113CP
CF110MP (B)
Manual WC Flush Valve
With Push Button



WGFA310114CP
UFSMP (B)
Manual Urinal Flush Valve
With Push Button



WGFA310102CP
CF - 110MPV-D
Concealed WC Flush Valve



WGFA310105CP
CF - 10MV-D
Exposed WC Flush Valve



WGFA310106CP
UF-3D
Exposed Urinal Flush Valve
with straight pipe



WGFA310108CP
UF-2D
Exposed Urinal Flush Valve
with 40 mm Offset